

KH 801

Fan heater for industrial enclosures

125 W - 1,300 W

RESISTOR HEATING TECHNOLOGY



INTEGRATED FAN

Compact fan provides uniform heat distribution inside the enclosure

ROBUST DESIGN

Aluminium housing in 3 different sizes

With AC or DC voltage available

HEATER INDICATOR

LED on when heating

THERMOSTAT

Thermostat allows to select the desired temperature inside the enclosure

FAN CONTROL SWITCH

Auto mode – fan operates only when heating
FAN ON mode - fan operates continuously to circulate the enclosure air



FEATURES

- Adjustable thermostat
- Indicator Light
- Fan Auto / ON switch
- Screw / DIN Clip mounting
- Operating temperature range
-20°C - 40°C / -4°F -+104°F

Order number	Power output	Fan air flow	Voltage / Frequency	Dimensions (H x W x D)
801125A44001	125 W	27 m ³ /h / 15.9 cfm	230 V - 50/60 Hz	137 x 111 x 116 mm 5.39 x 4.09 x 4.61 in
801125A33001	125 W	27 m ³ /h / 15.9 cfm	120 V - 50/60 Hz	137 x 111 x 116 mm 5.39 x 4.09 x 4.61 in
801125D22001	125 W	27 m ³ /h / 15.9 cfm	24 V DC	137 x 111 x 116 mm 5.39 x 4.09 x 4.61 in
801200A44001	200 W	27 m ³ /h / 15.9 cfm	230 V - 50/60 Hz	137 x 111 x 116 mm 5.39 x 4.09 x 4.61 in
801200A33001	200 W	27 m ³ /h / 15.9 cfm	120 V - 50/60 Hz	137 x 111 x 116 mm 5.39 x 4.09 x 4.61 in
801200D22001	200 W	27 m ³ /h / 15.9 cfm	24 V DC	137 x 111 x 116 mm 5.39 x 4.09 x 4.61 in
801400A44001	400 W	44 m ³ /h / 25.9 cfm	230 V - 50/60 Hz	190 x 111 x 116 mm 7.48 x 4.09 x 4.61 in
801400A33001	400 W	44 m ³ /h / 25.9 cfm	120 V - 50/60 Hz	190 x 111 x 116 mm 7.48 x 4.09 x 4.61 in
801800A44001	800 W	44 m ³ /h / 25.9 cfm	230 V - 50/60 Hz	190 x 111 x 116 mm 7.48 x 4.09 x 4.61 in
801800A33001	800 W	44 m ³ /h / 25.9 cfm	120 V - 50/60 Hz	190 x 111 x 116 mm 7.48 x 4.09 x 4.61 in
8011K4A44001	1300 W	83 m ³ /h / 48.8 cfm	230 V - 50/60 Hz	190 x 126 x 155 mm 7.48 x 4.96 x 6.10 in
8011K4A33001	1300 W	83 m ³ /h / 48.8 cfm	120 V - 50/60 Hz	190 x 126 x 155 mm 7.48 x 4.96 x 6.10 in
Certification	CE, cURus			

