

Air to Water Heat Exchanger



Description

Order Number:	752520B001
Brand Name:	SLIMLINE HEX
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	IP 55 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus

Technical data

Cooling capacity 95F/W50F (132 GPH):2800 W

Coolant: Water, light oils or similar

Operating temperature range: 1°C - 60°C

Air volume flow (system / unimpeded):560 / 800 m³/h

Mounting: Wandanbau / Halbeinbau

Dimension H x W x D: 1,350 x 395 x 192 (37+155) mm

Weight: 28 kg

Voltage / Frequency: 380-415 V 50 Hz 3~
400-460 V 60 Hz 3~

Starting current: 0.4 / 0.4 A

Max. current: 0.2 / 0.2 A

Power consumption: 75 W

Max. power: 70 / 105 W


Pressure water circuit: 10 bar

Water connection: Rp 1/2" - Innengewinde (mit optionalen Anschlüssen für Rohrrinnendurchmesser von 13 mm)

Fuse: 1 A (T)

Connection: 5-polige Anschlussklemme für Signale
4-polige Anschlussklemme für Spannung

Cut out dimensions:



Order Information

Stainless steel housing part no.	752520B62
Verpackungsmaße	1442 x 495 x 242 mm
Bruttogewicht	35 kg
Taric code	84158300