

Air to Water Heat Exchanger



Description


Order Number:	2149110
Brand Name:	SLIMLINE HEX
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	NEMA 12
Optional:	With waterflow regulator with magnetic valve (control range 68°F - +122°F) part no. 2149100
Approvals:	CE

Technical data


Cooling capacity 95F/W50F (53 GPH):	16380 BTU
Cooling capacity 95F/W50F (132 GPH):	19110 BTU
Coolant:	Water, light oils or similar
Operating temperature range:	+34°F - +161°F
Air volume flow (system / unimpeded):	576 / 883 cfm
Mounting:	Wall mounted
Dimension H x W x D:	55.12 x 18.11 x 9.53 in.
Weight:	72.75 lbs
Voltage / Frequency:	120 V ~ 60 Hz
Starting current:	5 A
Max. current:	2.6 A
Max. power:	300 W
Pressure water circuit:	10 bar
Water connection:	1/2" - inside thread with 2 connectors for pipe internal diameter of 0.51 in.
Fuse:	6 A (T)
Connection:	Connection terminals

Performance graph:

ΔT = Temperature difference between enclosure air and coolant
P = Cooling Capacity



Air flow:



Cut out dimensions:



Order Information

Stainless steel housing part no.	21491102
With solenoid valve part no.	2149100
Verpackungsmaße	1484 x 540 x 280 mm
Bruttogewicht	42.5 kg
Taric code	84158300
GTIN (EAN)	5350604211001