

## Electronic hygostat



### Description

|                            |                                     |
|----------------------------|-------------------------------------|
| <b>Order Number:</b>       | 301610                              |
| <b>Brand Name:</b>         | SOLIFLEX                            |
| <b>Housing Material:</b>   | PC plastic                          |
| <b>Ingress protection:</b> | IP 20                               |
| <b>Note:</b>               | Hyst. 5%r.H. / Sw.Pt.tol $\pm 10\%$ |
| <b>Approvals:</b>          | CE, cURus                           |

## Technical data

|                                     |                                                                                                                        |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Operating temperature range:</b> | -13 - 158°F / 95% int. sensor<br>-13 - 176°F / 95% ext. sensor                                                         |
| <b>Setting range:</b>               | 30 - 90 %                                                                                                              |
| <b>Mounting:</b>                    | DIN rail 1.38 inch                                                                                                     |
| <b>Dimension H x W x D:</b>         | 60 x 39 x 53,3 mm                                                                                                      |
| <b>Weight:</b>                      | 0.20 lbs.                                                                                                              |
| <b>Voltage / Frequency:</b>         | 24 V DC / 16 A                                                                                                         |
| <b>Lifetime:</b>                    | 100,000 hrs.                                                                                                           |
| <b>Connection:</b>                  | 4-polige Klemme, Anzugsmoment 0,5 Nm max.<br>Starrdrahtleitung 2,5 mm <sup>2</sup> , Litzenleitung 1,5 mm <sup>2</sup> |



## Order Information

|                        |               |
|------------------------|---------------|
| <b>Zolltarifnummer</b> | 90321089      |
| <b>EAN Nummer</b>      | 5350604010567 |