

Air / water heat exchanger



Description

Order Number:	750640B001
Brand Name:	SLIMLINE HEX
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 55 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus

Technical Data

Cooling capacity L35W10 (200 l/h):	700 W
Coolant:	Water, light oils or similar
Operating Temperature Range:	1°C - 60°C
Air flow volume (system / unimpeded):	110 / 220 m³/h
Mounting:	Wall mounted / recessed
Dimensions A x B x C (D+E):	600 x 250 x 127 (37 + 90) mm
Weight:	7.5 Kg
Voltage / Frequency:	120-230 V ~ 50/60 Hz
Starting current:	1.0 / 1.4 A
Max. current:	0.25 / 0.35 A
Max. power:	15 W
Pressure water circuit:	10 bar
Water connection:	Rp 3/8" - inside thread (with optional connectors for pipe internal diameter of 10 mm)
Fuse:	1 A (T)
Connection:	5 - pole terminal for signals 4 - pole terminal for power

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE HEX - air/water heat exchangers](#)

Order Information

Stainless steel AISI 304 (V2A) housing order no.	750640B62
Box dimensions	692 x 285 x 192 mm
Gross weight	9.5 Kg
Taric Code	84158300