

Filter Fan



Description

Order Number:	4411A3000
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus, CSA

Accessories:



[Hose-proof protection hood FC 4000 200](#)



[Hose-proof protection hood FC 4000 200 FDA](#)



[Adjustable Thermostat NO](#)

Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	130 m³/h
Static pressure:	100 Pa
Dimensions A x B x C (D+E):	204 x 204 x 95.5 mm
Weight:	1.2 kg
Cut out dimensions:	177 x 177 (+1.5) mm
Voltage / Frequency:	120 V ~ 60 Hz
Rated current:	0.18 A
Power consumption:	15 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1 - 2.1 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	44 dB(A)


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [m³/h]
 P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

In RAL 9005	4411A3003
With TYPE 3R protection part no.	4411A3033
Taric code	84145915
GTIN (EAN)	5350604100350