

Filter Fan



Description

Order Number:	4830A4100
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Note:	Reverse air flow
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus

Accessories:



[Hose-proof protection hood FC 4000 400](#)



[Hose-proof protection hood FC 4000 400 FDA](#)



[Adjustable Thermostat NO](#)

Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	540 m³/h
Static pressure:	207 Pa @ 50Hz / 221 Pa @ 60Hz
Dimensions A x B x C (D+E):	325 x 325 x 160.2 mm
Weight:	3.62 kg
Cut out dimensions:	291 x 291 (+1.5) mm
Voltage / Frequency:	230 V ~ 50/60 Hz
Rated current:	0.31 A / 0.35 A
Power consumption:	70 W / 85 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	65.3 dB(A) @ 50 Hz 68.1 dB(A) @ 60 Hz


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [m³/h]
 P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

In RAL 9005	4830A4103
Taric code	84145915
GTIN (EAN)	5350604100626