




Control Cabinet Air Conditioner



Description


Order Number:	43090001
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
IP protection class to EN 60 529:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus
Accessories:	<div style="display: flex; align-items: center; margin-bottom: 10px;">  <div style="margin-left: 10px;">Stainless Steel Filter Holder 4305/08/09/10</div> </div> <div style="display: flex; align-items: center; margin-bottom: 10px;">  <div style="margin-left: 10px;">Fibre Filter Media 4305/08/09/10</div> </div> <div style="display: flex; align-items: center;">  <div style="margin-left: 10px;">Washable Aluminium Filter 4305/08/09/10</div> </div>

Technical Data


Cooling capacity L35L35 (EN14511-3):	850 W @ 50 Hz 880 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	640 W @ 50 Hz 665 W @ 60 Hz
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	180 g / 6.3 oz
High / low Pressure:	29.5 / 6 bar 425 / 88 psig
Air flow volume (system / unimpeded):	Ambient air circuit: 435 / 550 m ³ /h Cabinet air circuit: 200 / 250 m ³ /h
Operating Temperature Range:	10°C - 55°C
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	651.4 x 315 x 260 mm
Weight:	30 kg
Cut out dimensions:	635 x 275 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	3.0 A @ 50 Hz 3.2 A @ 60 Hz
Starting current:	15.9 A
Max. current:	4.1 A
Nominal power L35L35:	530 W @ 50 Hz 610 W @ 60 Hz
Max. power:	810 W
Fuse:	10 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.
More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT INDOOR - reliable and economical](#)

Performance graph:


click image to enlarge

Air flow:


click image to enlarge

Cut Out Dimension:


click image to enlarge

Order Information

Stainless steel housing part no.	4309002
With condensate evaporation part no.	43090101
Box dimensions	685 x 353 x 295 mm
Gross weight	31.5 kg
Taric code	84158200