

Thermoelectric cooling unit



Description

Order Number:	388708-3
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm. Niehoff part no. 388708-3
Approvals:	CE, cURus

Technical Data


Cooling capacity L35L35 (EN14511-3):	75 W
Air flow volume (system / unimpeded):	Ambient air circuit: 116 / 306 m³/h Cabinet air circuit: 58 / 182 m³/h
Operating Temperature Range:	-20°C - 70°C
UL temperature range:	-20°C - 65°C
Mounting:	Recessed / Wall mounted
Dimensions A x B x C (D+E):	250 x 203 x (86+74) mm
Cut out dimensions:	210 x 160 mm
Voltage / Frequency:	24 V DC
Current L35L35:	4.6 A
Starting current:	6.9 A
Max. current:	5.3 A
Power consumption:	110 W
Max. power:	127 W
Fuse:	8 A (T)
Connection:	6 pole terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SOLITHERM PELTIER - cooling units without refrigerant](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Dimensions:



[click image to enlarge](#)