

## Electronic hygostat



## Description

<b>Order Number:</b>	301610
<b>Brand Name:</b>	SOLIFLEX
<b>Housing Material:</b>	PC plastic
<b>Ingress Protection:</b>	IP 20
<b>Note:</b>	Hyst. 5%r.H. / Sw.Pt.tol $\pm 10\%$
<b>Approvals:</b>	CE, cURus

## Technical Data

**Operating Temperature Range:** -25 - 70°C / 95% int. sensor  
-25 - 80°C / 95% ext. sensor

---

**Setting range:** 30 - 90 %

---

**Mounting:** DIN Rail 35 mm

---

**Dimensions A x B x C (D+E):** 60 x 39 x 53,3 mm

---

**Weight:** 60 g

---

**Voltage / Frequency:** 24 V DC / 16 A

---

**Lifetime:** 100,000 hrs.

---

**Connection:** 4-pole terminal, clamping torque 0.5 Nm max.  
solid wire - 2.5 mm<sup>2</sup> max., stranded wire - 1.5 mm<sup>2</sup> max.

---

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - accessories for safety inside enclosures](#)



## Order Information

<b>Taric code</b>	90321089
<b>GTIN (EAN)</b>	5350604010567