

Filterless enclosure cooling unit



Description

Order Number:	4274202
Brand Name:	SLIMLINE
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus
Accessories:	 NEMA 4X Cover 4274

Technical Data


Cooling capacity L35L35 (EN14511-3):	1500 W @ 50 Hz 1500 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	1200 W
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R 513A / 630
Refrigerant charge:	535 g / 18.9 oz
High / low Pressure:	40 / 13 bar 580 / 198 psig
Air flow volume (system / unimpeded):	Ambient air circuit: 430 / 1200 m³/h Cabinet air circuit: 200 / 850 m³/h
Operating Temperature Range:	10°C - 55°C
Mounting:	Wall mounted / Recessed
Dimensions A x B x C (D+E):	1,550 x 395 x 145 (25+120) mm
Weight:	50 kg
Cut out dimensions:	1,531 x 376 mm
Voltage / Frequency:	380-415 V 50 Hz 3~ 400-460 V 60 Hz 3~
Current L35L35:	1.9 A @ 50 Hz 2.0 A @ 60 Hz
Starting current:	13 A
Max. current:	2.3 A
Nominal power L35L35:	990 W @ 50 Hz 1220 W @ 60 Hz
Max. power:	1450 W
Fuse:	3 x 6 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	13 A
Full load current fans:	3.2 A
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE - filterless cooling units](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Box dimensions

Gross weight

Taric code

84158200

GTIN (EAN)

5350604371392