

CU Connect. Roof 1.5kW IP54



Description

Order Number:	950600001
Brand Name:	SLIMLINE PRO TOP
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54
Approvals:	CE


Technical Data

Cooling capacity L35L35 (EN14511-3):	650 W
Cooling capacity L35L50 (EN14511-3):	580W
Compressor type:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	120 g / 4.23 oz.
High / low Pressure:	28 / 6 bar 406 / 87 psig
Operating Temperature Range:	5°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 408 m ³ /h Enclosure air circuit: 265 m ³ /h
Mounting:	Roof mounted
Dimensions A x B x C (D+E):	368 x 400 x 325 mm
Weight:	16.4 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	1.7 / 1.6 A
Starting current:	6 A
Max. current:	2.2 A
Nominal power L35L35:	337 W
Fuse:	15 A (T)
Short-circuit current rating:	5 kA
Connection:	4 pole connector for power 5 pole connector for signals 3 pole connector for RS 485 MODBUS


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE PRO TOP - roof mounted cooling units](#)

Performance graph:


[click image to enlarge](#)

Cut Out Dimension:


[click image to enlarge](#)

Order Information

Stainless steel housing part no.

95060002

Taric Code

84158200