





## Cabinet cooling unit



### Description

<b>Order Number:</b>	852010001
<b>Brand Name:</b>	SLIMLINE PRO
<b>Colour:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>IP protection class to EN 60 529:</b>	IP 55 / Type 12
<b>Approvals:</b>	CE, cURus, cULus
<b>Accessories:</b>	<div style="display: flex; align-items: center; margin-bottom: 10px;">  <p>Gasket Kit Type 4</p> </div> <div style="display: flex; align-items: center; margin-bottom: 10px;">  <p>Cold Air Outlet Duct 8515/20/25</p> </div> <div style="display: flex; align-items: center; margin-bottom: 10px;">  <p>Washable Aluminium Filter 8515/20/25</p> </div> <div style="display: flex; align-items: center;">  <p>Vibration Protection Kit 2</p> </div>

## Technical Data


<b>Cooling capacity L35L35 (EN14511-3):</b>	2000 W @ 50 Hz 2100 W @ 60 Hz
<b>Cooling capacity L35L50 (EN14511-3):</b>	1850 W @ 50 Hz 1850 W @ 60 Hz
<b>EER L35L35:</b>	2.0
<b>Compressor type:</b>	Rotary piston
<b>Refrigerant / GWP:</b>	R 513A / 630
<b>Refrigerant charge:</b>	410 g / 14.5 oz
<b>High / low Pressure:</b>	31 / 6 bar 450 / 88 psi
<b>Air flow volume (system / unimpeded):</b>	Ambient air circuit: 680 / 1200 m <sup>3</sup> /h Cabinet air circuit: 500 / 850 m <sup>3</sup> /h
<b>Operating Temperature Range:</b>	10°C - 60°C
<b>UL temperature range:</b>	10°C - 60°C
<b>Mounting:</b>	Wall mounted / recessed
<b>Dimensions A x B x C (D+E):</b>	1,350 x 395 x 210 (55+155) mm
<b>Weight:</b>	49.5 kg
<b>Voltage / Frequency:</b>	120 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Current L35L35:</b>	8.8 A @ 50 Hz 11.2 A @ 60 Hz
<b>Starting current:</b>	32 A
<b>Max. current:</b>	14.8 A
<b>Nominal power L35L35:</b>	1010 W @ 50 Hz 1240 W @ 60 Hz
<b>Max. power:</b>	1690 W
<b>Fuse:</b>	20 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	8 A

<b>Full load current fans:</b>	1.5 A
<b>Connection:</b>	4 pole terminal block for power 5 pole terminal block for signals 3 pole terminal block for RS 485


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

**Performance graph:**


[click image to enlarge](#)

**Cut Out Dimension:**


[click image to enlarge](#)

## Order Information

<b>Box dimensions</b>	1442 x 495 x 242 mm
<b>Gross weight</b>	54 Kg
<b>Taric code</b>	84158200