


## Filterless enclosure cooling unit



## Description

<b>Order Number:</b>	4269102
<b>Brand Name:</b>	SLIMLINE
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress Protection:</b>	IP 54 / TYPE 12
<b>Approvals:</b>	CE, cURus, cULus
<b>Accessories:</b>	 <a href="#">NEMA 4X Cover 4269</a>




## Technical Data

<b>Cooling capacity L35L35 (EN14511-3):</b>	520 W
<b>Cooling capacity L35L50 (EN14511-3):</b>	180 W
<b>Compressor type:</b>	Rotary piston compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	147 g / 5.2 oz
<b>High / low Pressure:</b>	17 / 15 bar 250 / 220 psig
<b>Operating Temperature Range:</b>	10°C - 50°C
<b>Air flow volume (system / unimpeded):</b>	Ambient air circuit: 250 / 650 m <sup>3</sup> /h Cabinet air circuit: 125 / 250 m <sup>3</sup> /h
<b>Mounting:</b>	Wall mounted / Recessed
<b>Dimensions A x B x C (D+E):</b>	600 x 320 x 110 (25+85) mm
<b>Weight:</b>	15.8 kg
<b>Cut out dimensions:</b>	581 x 301 mm
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Current L35L35:</b>	4.5 A
<b>Starting current:</b>	14.6 A
<b>Max. current:</b>	5.3 A
<b>Nominal power L35L35:</b>	475 W
<b>Max. power:</b>	550 W
<b>Fuse:</b>	6 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	15.2 A
<b>Full load current fans:</b>	5.3 A
<b>Connection:</b>	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE - filterless cooling units](#)

**Performance graph:**

[click image to enlarge](#)
**Air flow:**

[click image to enlarge](#)
**Cut Out Dimension:**

[click image to enlarge](#)

## Order Information

<b>Box dimensions</b>	680 x 400 x 155 mm
<b>Gross weight</b>	19 kg
<b>Tarcic code</b>	84158200
<b>GTIN (EAN)</b>	5350604370685