

Outdoor filter fan SF 4732 - 120V



Description

Order Number:	4732182503
Brand Name:	SOLIVENT PRO
Colour:	RAL 9005
Housing Material:	PC plastic
IP protection class to EN 60 529:	IP 54
UL Typ (UL 50E):	12, 3R
Approvals:	CE, cURus, cULus
UL File Number:	E498756

Technical Data


Air flow unimpeded IP 54:	810 / 851 m³/hr
Air flow with exhaust filter IP 54:	535 / 570 m³/hr
Operating Temperature Range:	-40°C - 70°C
Storage temperature range:	-40°C - 70°C
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	325.5 x 325.5 x 165.2 (11.6+153.6) mm
Cut out dimensions:	292 x 292 mm
Voltage / Frequency:	120 V ~ 50/60 Hz
Rated current:	1.18 / 1.67 A
Power consumption:	135 / 190 W
Wall thickness:	1-3 mm
Noise level:	71 dB(A)
Fuse:	1.5 A (T)
Connection:	Spring terminal

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SOLIVENT PRO - Filter fans & exhaust filters](#)

Air flow:




[click image to enlarge](#)

Cooling capacity:



[click image to enlarge](#)

Dimensions:



[click image to enlarge](#)

Order Information

Order number	IP rating	UL Type	RAL colour	Flow type ¹⁾	Air flow (m ³ /h) ²⁾	Air flow with exhaust filter (m ³ /h)
4732182503	54	12 / 3R	RAL 9005	B	810 / 851 m ³ /hr	535 / 570 m ³ /hr
473218R2501	54	12 / 3R	RAL 7035	S	652 / 717 m ³ /hr	
473218R2503	54	12 / 3R	RAL 9005	S	652 / 717 m ³ /hr	

¹⁾ B = Blowing – from ambient into the enclosure (standard version)
 S = Suction – from enclosure to ambient (on request)

²⁾ unimpeded 50/60 Hz