


Cabinet cooling unit




Description

Order Number:	850620S62
Brand Name:	SLIMLINE PRO
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 56 / Type 12, 3, 3R, 4, 4X
Approvals:	CE, cURus, cULus
Accessories:	



[Cold Air Outlet Duct 8503/06](#)



[Washable Aluminium Filter 8503/06](#)

Technical Data



Cooling capacity L35L35 (EN14511-3):	700 W @ 50 Hz 750 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	620 W @ 50 Hz 655 W @ 60 Hz
EER L35L35:	1.6 / 1.7
Compressor type:	Rotary piston
Refrigerant / GWP:	R 513A / 630
Refrigerant charge:	127 g / 4.5 oz
High / low Pressure:	28 / 6 bar 406 / 88 psi
Air flow volume (system / unimpeded):	Ambient air circuit: 225 / 408 m ³ /h Cabinet air circuit: 122 / 180 m ³ /h
Operating Temperature Range:	10°C - 55°C
UL temperature range:	10°C - 55°C
Mounting:	Wall mounted / recessed
Dimensions A x B x C (D+E):	600 x 250 x 187.6 (48.6+139) mm
Weight:	16 kg
Voltage / Frequency:	400V/460 V - 50/60 Hz 2~
UL Voltage / Frequency:	460 V / 60Hz 2~
Current L35L35:	1.2 A @ 50Hz 1.2 A @ 60 Hz
Starting current:	3.0 A
Max. current:	1.6 A
Nominal power L35L35:	440 W @ 50 Hz 440 W @ 60 Hz
Max. power:	620 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	1 A

Full load current fans:	0.15 A
Connection:	4 pole terminal block for power 5 pole terminal block for signals 3 pole terminal block for RS 485

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

Performance graph:

[click image to enlarge](#)
Cut Out Dimension:

[click image to enlarge](#)

Order Information

Box dimensions	692 x 350 x 242 mm
Gross weight	17 Kg
Taric code	84158200