Filter Fan



Description

Order Number:	4210A4000
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus, CSA
Accessories:	 Hose-proof protection hood FC 4000 100
	 Hose-proof protection hood FC 4000 100 FDA
	 Adjustable Thermostat NO


Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	67 m³/h
Static pressure:	73 Pa @ 50 Hz 86 Pa @ 60 Hz
Dimensions A x B x C (D+E):	150 x 150 x 73 mm
Weight:	0.8 kg
Cut out dimensions:	124 x 124 (+1.5) mm
Voltage / Frequency:	230 V ~ 50/60 Hz
Rated current:	0.13 A / 0.10 A
Power consumption:	18 W / 16 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1 - 2.1 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	40 dB(A) @ 50 Hz 44 dB(A) @ 60 Hz

Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group SOLIFLEX - Filter fans & exhaust filters


Air flow:


Q = Air flow [m3/h]
P = Static pressure [Pa]



click image to enlarge

Cut Out Dimension:





click image to enlarge

Order Information

In RAL 9005	4210A4003
With TYPE 3R protection part no.	4210A4033
Taric code	84145915
GTIN (EAN)	5350604100220