Filter Fan



Description

Order Number:	4610D7100
Brand Name:	SOLIFLEX
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54, Type 12, 3R
Note:	Reverse air flow
Optional:	Different housing colors available on request
Approvals:	CE, cURus, cULus, CSA
Accessories:	 Hose-proof protection hood FC 4000 300
	 Hose-proof protection hood FC 4000 300 FDA
	 Adjustable Thermostat NO


Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	225 m³/h
Static pressure:	140 Pa
Dimensions A x B x C (D+E):	250 x 250 x 124.2 mm
Weight:	1.4 kg
Cut out dimensions:	223 x 223 (+1.5) mm
Voltage / Frequency:	48 V DC
Rated current:	0.34 A
Power consumption:	16 W
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 according to EN 779
Installation:	Elastic clips
Noise level:	60 dB(A)

Please click on the graphics to download.
More CAD drawings can be found under Product Download.
> Overview Product Group SOLIFLEX - Filter fans & exhaust filters


Air flow:


Q = Air flow [m3/h]
P = Static pressure [Pa]



click image to enlarge

Cut Out Dimension:





click image to enlarge

Order Information

In RAL 9005	4610D7103
Taric code	84145915
GTIN (EAN)	5350604100473