

Filter Fan



Description

Order Number:	4833A3100
Colour:	RAL 7035
Housing Material:	ABS Plastic
Ingress Protection:	IP 54
Optional:	Different housing colours available on request With NEMA 3R protection part no. 4833A3130
Approvals:	CE, cULus, CSA

Technical Data

Operating Temperature Range:	-10°C - 55°C
Air flow unimpeded:	840 m³/h
Static pressure:	320 Pa
Dimensions A x B x C (D+E):	325 x 325 x 160.2
Weight:	4.25 kg
Cut out dimensions:	291 +1.5 x 291 +1.5
Voltage / Frequency:	120 V ~ 60 Hz
Rated current:	1.93 A
Power consumption:	225 W
Degree of separation:	85% - DIN 24185
Wall thickness:	1.5 - 2.5 mm
Filter class:	G3 gemäß EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	78.9 dB(A)


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SOLIFLEX - Filter fans & exhaust filters](#)


Air flow:

Q = Air flow [m³/h]
 P = Static pressure [Pa]



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

With NEMA 3R protection part no.	4833A3130
Taric code	84145915
GTIN (EAN)	5350604100688