

Outdoor cooling unit




Description

Order Number:	571000001
Brand Name:	Compact Outdoor
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 56 / Type 12, 3, 3R, 4
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical Data

Cooling capacity L35L35 (EN14511-3):	1.00 kW @ 50 Hz 1.08 kW @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	660 W @ 50 Hz 720 W @ 60 Hz
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	210 g / 7.4 oz
High / low Pressure:	30.5 / 6 bar 445 / 88 psig
Operating Temperature Range:	-40°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 320 / 850 m ³ /h Cabinet air circuit: 375 / 550 m ³ /h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	900 x 304 x 270 mm
Weight:	38 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	4.0 A @ 50 Hz 4.2 A @ 60 Hz
Starting current:	16 A
Max. current:	4.5 A
Nominal power L35L35:	770 W @ 50 Hz 830 W @ 60 Hz
Max. power:	1.15 kW
Fuse:	9 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.
More CAD drawings can be found under [Product Download](#).
> [Overview Product Group COMPACT OUTDOOR - OLD](#)

Performance graph:


[click image to enlarge](#)

Cut Out Dimension:


[click image to enlarge](#)

Order Information

Without 400 W enclosure heater part no.	571000001
With 400 W enclosure heater part no.	571001001
Box dimensions	940 x 348 x 310 mm
Gross weight	40 kg
Taric code	84158200