

Cabinet cooling unit



Description

Order Number: 850600001

Brand Name: SLIMLINE PRO

Colour: RAL 7035

Housing Material: Mild steel, powder coated

Ingress Protection: IP 55 / Type 12

Approvals: CE, cURus, cULus


Accessories:



Gasket Kit Type 4



Cold Air Outlet Duct 8503/06



Washable Aluminium Filter 8503/06



External Transformer 400/460 V 2~

Technical Data

Cooling capacity L35L35:	670 W @ 50 Hz 680 W @ 60 Hz
Cooling capacity L35L50:	435 W @ 50 Hz 450 W @ 60 Hz
EER L35L35:	1.55
Compressor type:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	117 g / 3.46 oz.
High / low Pressure:	28 / 6 bar 406 / 88 psi
Operating Temperature Range:	10°C - 60°C
UL temperature range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 200 / 408 m³/h Cabinet air circuit: 122 / 180 m³/h
Mounting:	Wall mounted / recessed
Dimensions A x B x C (D+E):	600 x 250 x 135 (45+90) mm
Weight:	14 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	2 A @ 50 Hz 1.9 A @ 60 Hz
Starting current:	6 A
Max. current:	2.7 A
Nominal power L35L35:	410 W @ 50 Hz 430 W @ 60 Hz
Max. power:	620 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	1.6 A


Full load current fans:	0.2 A
Connection:	4 pole terminal block for power 5 pole terminal block for signals 3 pole terminal block for RS 485

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Box dimensions	692 x 285 x 192 mm
Gross weight	16 Kg
Taric code	84158200
GTIN (EAN)	5350604390027