

SLIMLINE PRO TOP

Roof mounted cooling units



- Modern industrial design
- Up to 50% less refrigerant
- Operating temperature range from 5°C to 55°C
- High protection class IP 54
- Available with stainless steel housing
- Identical cutout for multiple cooling capacities



KG 9515

SLIMLINE PRO TOP

For when no other space is available

- ✓ Cooling capacities from 600 W up to 4 kW
- ✓ Microchannel condenser allows significant reduction in refrigerant charge resulting in a lower CO₂ equivalent
- ✓ Maximum cooling power with minimum space
- ✓ Digital controller with display
- ✓ Enhanced protection class of IP 54 / UL Type 12
- ✓ Also with stainless steel housing
- ✓ Temperature range 5°C - 55°C



Model	KG 9506		KG 9508		KG 9512		KG 9515		
Order number	950600001	950800001	950820001	951200001	951220001	951500001	951520001		
Order no. in stainless steel 304	95XXX002								
Cooling capacity L35L35	600 W	800 W		1.2 kW		1.5 kW			
Cooling capacity L35L50	580 W	600 W		800 W		1.2 kW			
Compressor type	Rotary piston								
Operating temperature range	5°C - 55°C								
Setting range	25°C - 50°C								
System air flow	265 m ³ /h	645 m ³ /h		645 m ³ /h		645 m ³ /h			
Unimpeded air flow	408 m ³ /h	850 m ³ /h		850 m ³ /h		850 m ³ /h			
Mounting	Roof mounted								
Dimensions L x W x H	368 x 400 x 325 mm		412 x 595 x 395 mm						
Housing material / colour	Mild steel powder coated, RAL 7035								
Weight	16.8 kg	27.5 kg	32 kg	34.5 kg	39 kg	34.5 kg	39 kg		
ELECTRICAL DATA									
Voltage / Frequency	230 V ~ 50/60 Hz	230 V ~ 50/60 Hz	400 / 460 V 50/60 Hz 2~	230 V ~ 50/60 Hz	400 / 460 V 50/60 Hz 2~	230 V ~ 50/60 Hz	400 / 460 V 50/60 Hz 2~		
Current L35L35 ¹⁾	1.7 / 1.6 A	2.3 / 2.5 A	1.4 / 1.5 A	3.0 / 3.6 A	1.7 / 2.0 A	3.3 / 4.0 A	1.9 / 2.2 A		
Starting current	6 A	6 A	4 A	16 A	8 A	16 A	8 A		
Max. current	2.2 A	3 A	1.9 A	4.3 A	2.2 A	6.1 A	3 A		
Nominal power L35L35 ¹⁾	340 / 360 W	490 / 578 W	537 / 617 W	650 / 880 W	700 / 930 W	700 / 895 W	760 / 955 W		
Max. power	495 W	680 W	719 W	966 W	1 kW	1.15 kW	1.65 kW		
Fuse rating	15 A(T)	15 A(T)	15 A(T)	15 A(T)	15 A(T)	15 A(T)	15 A(T)		
Connection	4 - pole connector for power, 5 - pole connector for signals								
Ingress protection	IP 54								
Certification	CE, cURus								

¹⁾ Values for 50/60 Hz

Modern industrial design

Digital controller with display

Microchannel condenser allows 50% less refrigerant charge and higher efficiency



KG 9540

Model	KG 9520		KG 9530	KG 9540
Order number	952000001	952020001	953020001	954020001
Order no. in stainless steel 304	95XXX002			
Cooling capacity L35L35	2.0 kW		3.0 kW	4.0 kW
Cooling capacity L35L50	1.6 kW	1.5 kW	2.64 kW	3.3 kW
Compressor type	Rotary piston			
Operating temperature range	5°C - 55°C			
Setting range	25°C - 50°C			
System air flow	602 m ³ /h	630 m ³ /h	1233 m ³ /h	1233 m ³ /h
Unimpeded air flow	1200 m ³ /h	1200 m ³ /h	1400 m ³ /h	1400 m ³ /h
Mounting	Roof mounted			
Dimensions L x W x H	435 x 595 x 475 mm		456 x 795 x 575 mm	
Housing material / colour	Mild steel powder coated, RAL 7035			
Weight	38.1 kg	40.1 kg	54.2 kg	57.2 kg
ELECTRICAL DATA				
Voltage / Frequency	230 V ~ 50/60 Hz	400 / 460 V 50/60 Hz 3~	400 / 460 V 50/60 Hz 3~	400 / 460 V 50/60 Hz 3~
Current L35L35 ¹⁾	3.9 / 5.0 A	1.7 / 1.8 A	2.9 / 2.8 A	3.2 / 3.3 A
Starting current	22 A	13 A	20 A	28 A
Max. current	6.4 A	2.4 A	3.2 A	4.1 A
Nominal power L35L35 ¹⁾	870 / 1.1 kW	880 / 1.1 kW	1.16 / 1.50 kW	1.48 / 1.90 kW
Max. power	1.44 kW	1.6 kW	1.97 kW	2.6 kW
Fuse rating	15 A(T)	15 A(T)	15 A(T)	15 A(T)
Connection	4 - pole connector for power, 5 - pole connector for signals			
Ingress protection	IP 54			
Certification	CE, cURus			

¹⁾ Values for 50/60 Hz

SEIFERT SYSTEMS GmbH**Germany**

Albert-Einstein-Str. 3
42477 Radevormwald
+49 2195 68994-0
info.de@seifertsystems.com

SEIFERT SYSTEMS Ltd.**Skandinavia / Baltic States**

Sales office
25421 Pinneberg
+49 2195 68994-40
info.sk@seifertsystems.com

SEIFERT SYSTEMS Ltd.**Malta**

HF 09/10, Hal Far Ind. Estate
BBB 3000 Birzebbuga
+356 2220 7000
info@seifertsystems.com

SEIFERT SYSTEMS SA**France**

Wilerstraße 16
4563 Gerlafingen
+33 7 65298156
info.fr@seifertsystems.com

SEIFERT SYSTEMS GmbH**Austria**

Bärnthäl 1
4901 Ottmang am Hausruch
+43 7676 207120
info.at@seifertsystems.com

SEIFERT SYSTEMS Inc.**USA**

75 Circuit Dirve
North Kingstown, RI 02852
+1 401-294-6960
info.us@seifertsystems.com

SEIFERT SYSTEMS AG**Switzerland**

Wilerstraße 16
4563 Gerlafingen
+41 32 6753551
info.ch@seifertsystems.com

C.D. Automation Pvt. Ltd.**India**

8, Parsee Church Street
Kolkata - 7000 001
+91 33 2215 7080
info@seifertsystems.com

SEIFERT SYSTEMS Ltd.**Italy**

Sales office
26100 Cremona
+39 349 2594524
info.it@seifertsystems.com

SEIFERT SYSTEMS Pty Ltd.**Australia**

105 Lewis Road
Victoria 3152
+61 3 98011906
info@seifertsystems.com.au