

# SLIMLINE NEO ENCLOSURE COOLING

---

**SEIFERT SYSTEMS**

THERMAL MANAGEMENT FOR ENCLOSURES AND MACHINERY





# NEW ENCLOSURE COOLING SLIMLINE NEO

## F-Gas compliant, PFAS-free, future-proof

With the stricter F-Gas regulation and the threat of PFAS bans, it is clear that industry must switch to more climate-friendly refrigerants. Seifert reacted early. The solution: the new SLIMLINE NEO cooling units with the natural refrigerant R290. A milestone in industrial air conditioning, opening the direct path to a sustainable, safe, and economical future for companies.

## SLIMLINE NEO 4 KEY ADVANTAGES FOR INDUSTRY

1

**FUTURE-PROOF**  
in just one step



With SLIMLINE NEO, industrial companies can future-proof their operations in just one step: The natural refrigerant R290 used meets the upcoming requirements of the F-Gas Regulation EU 2024/573 and is PFAS-free.

2

**HIGHLY EFFICIENT**  
through state-of-the-art technology



SLIMLINE NEO achieves very high energy efficiency: The excellent thermodynamic properties of R290 and the inverter technology used deliver an outstanding EER of up to 3.6.

3

**CERTIFIED**  
for safe operation



All models of SLIMLINE NEO ensure safe operation in accordance with IEC/EN/UL 60335-2-40 and are certified according to the international standards ISO 9001 and ISO 14001.

4

**LOW EMISSIONS**  
for a low CO<sub>2</sub> footprint



With SLIMLINE NEO, industrial companies cool in a climate-friendly way: The low GWP of 0.02 of R290, the small amount of refrigerant used and the high energy efficiency reduce CO<sub>2</sub> emissions during operation.



# INNOVATIVE TECHNOLOGY, INNOVATIVE DESIGN

## SLIMLINE NEO – a statement for responsibility, efficiency and future viability

The key of the SLIMLINE NEO concept is the use of the natural, high-performance refrigerant R290, efficiently combined with energy-saving inverter technology. For SLIMLINE NEO, Seifert has developed a completely new housing that impresses with its compact and safe architecture, modern design, and optional customisation. With the new SLIMLINE NEO cooling units, Seifert customers are switching directly to the technology of the future.

### The refrigerant R290 – powerful and environmentally friendly

The refrigerant R290 is PFAS-free due to its natural composition and has an extremely low GWP of only 0.02. One kilogram of R290 with a GWP of 0.02 therefore has the same greenhouse effect as 20 grams of CO<sub>2</sub> (GWP 1), a fraction of the climate impact of chemical refrigerants. Due to its excellent thermodynamic properties, R290 delivers full cooling power even at high ambient temperatures and generates high cooling capacity with a small amount of refrigerant.

- R290 is climate-friendly, F-gas compliant and does not fall under PFAS bans.
- SLIMLINE NEO requires only 25 % of the refrigerant in comparable cooling units.

### The inverter technology – highly efficient and sustainable

The new cooling units feature inverter technology throughout. Unlike an on/off compressor, the inverter continuously regulates the speed of the compressor and fans. It perfectly adjusts the cooling capacity to the demand, keeping the temperature inside the enclosure stable and reducing condensation, resulting in an extended service life of sensitive components and electronics.

- The largest model of the SLIMLINE NEO achieves an EER of up to 3.6.
- The combination of refrigerant and inverter technology produces a significantly better climate footprint.



### Certified according to international standards

The SLIMLINE NEO unit architecture meets all safety requirements regarding the classification of R290 as a Class A3 refrigerant according to IEC/EN/UL 60335-2-40. SLIMLINE NEO is manufactured at sites certified according to the international standards ISO 9001:2015 and ISO 14001:2015.

Industrial Design by oundo.com

### The housing architecture – one cutout for three mounting options

For SLIMLINE NEO, Seifert has completely redesigned the technical and functional design, including customisable lighting options. The compact construction makes the cooling unit exceptionally lightweight and vibration-free. For maximum operational safety, the housing is also designed to prevent refrigerant from leaking into the enclosure.

- SLIMLINE NEO is almost a third smaller than similar cooling units.
- The low-vibration design improves component protection.

### The design – elegant surfaces and customization

The elegant design is available with a choice of surfaces made of powder-coated sheet metal or stainless steel.

Both surfaces and lighting can optionally be colour matched to the customer's brand identity.

Upon request, Seifert also manufactures tailor made solutions for individual customer requirements.

# ONE STEP, NO RISK

## SLIMLINE NEO – applications and technical data

Wherever sensitive electronics or processes need to be cooled, SLIMLINE NEO demonstrates its strengths: durable, reliable, compliant, and sustainable. This includes Mechanical and Plant Engineering, Food and Beverage Industry, IT and Telecommunications, Renewable Energies, Battery Storage, Automotive Industry as well as Environmental and Medical Technology.



Medical technology



Environmental



Automotive



Renewable energies



Battery storage



Telecommunication



IT technology



Food & Beverage



Mechanical



Plant construction



Learn more about SLIMLINE NEO at:  
[www.seifert-slimlineneo.com](http://www.seifert-slimlineneo.com)

Three cooling capacities  
and housing sizes  
SLIMLINE NEO is available in  
three versions. The design is  
similar for all models.



Model	KG 9210		KG 9215		KG 9225	
Order no.	921000001	921020001	921500001	921520001	922500001	922520001
Order no. stainless steel 304 (V2A)	921000002	921020002	921500002	921520002	922500002	922520002
Optimised operating point	1000 W		1500 W		2500 W	
Cooling capacity range	300 – 1100 W		500 – 1800 W		600 – 2700 W	
Compressor type	BLDC Rotary Piston					
Operating temperature range	10°C to 60°C					
Mounting	Wall mounted, recessed <sup>1)</sup> , internal <sup>2)</sup>					
Dimensions (H x W x D)	950 x 395 x 192 (137) <sup>2)</sup> mm		950 x 395 x 255 (100) <sup>1)</sup> (200) <sup>2)</sup> mm		1350 x 395 x 290 (135) <sup>1)</sup> (235) <sup>2)</sup> mm	
Cutout (H x W)	910 x 345 mm				1316 x 351 mm	
Housing material/Colour	Mild steel powder coated/RAL 7035, stainless steel					
Weight	25 kg	30 kg	28 kg	34 kg	36 kg	42 kg
Voltage/Frequency	120 – 230 V ~ 50/60 Hz	360 – 480 V 2~ 50/60 Hz	120 – 230 V ~ 50/60 Hz	360 – 480 V 2~ 50/60 Hz	120 – 230 V~ 50/60 Hz	360 – 480 V 2~ 50/60 Hz
EER	≤2.6		≤3.6		≤3.1	
Protection class	IP 55, Type 12, 3, 3R					
Connection	4 pole terminal block for power, 5 pole terminal block for signals, 3 pole terminal block for RS 485					
Fuse	20 A (T)					

<sup>1)</sup> unit section protruding into the enclosure / <sup>2)</sup> unit section protruding into the enclosure

**SEIFERT SYSTEMS GmbH****Germany**

Albert-Einstein-Str. 3  
42477 Radevormwald  
+49 2195 68994-0  
info.de@seifertsystems.com

**SEIFERT SYSTEMS Ltd.****Skandinavia/Baltic States**

Sales office  
25421 Pinneberg  
+49 2195 68994-40  
info.sk@seifertsystems.com

**SEIFERT SYSTEMS Ltd.****Malta**

HF 09/10, Hal Far Ind. Estate  
BBG 3000 Birzebbuga  
+356 2220 7000  
info@seifertsystems.com

**SEIFERT SYSTEMS SA****France**

Wilerstrasse 16  
4563 Gerlafingen  
+33 7 65298156  
info.fr@seifertsystems.com

**SEIFERT SYSTEMS GmbH****Austria**

Bärnthal 1  
4901 Ottmang am Hausruck  
+43 7676 207120  
info.at@seifertsystems.com

**SEIFERT SYSTEMS Inc.****USA**

75 Circuit Drive  
North Kingstown, RI 02852  
+1 401-294-6960  
info.us@seifertsystems.com

**SEIFERT SYSTEMS AG****Switzerland**

Wilerstrasse 16  
4563 Gerlafingen  
+41 32 6753551  
info.ch@seifertsystems.com

**SEIFERT SYSTEMS Ltd.****India**

Sales Office  
Kolkata – 7000 001  
+91 33 2215 7080  
info@seifertsystems.com

**SEIFERT SYSTEMS Ltd.****Italy**

Sales office  
26100 Cremona  
+39 349 2594524  
info.it@seifertsystems.com

**SEIFERT SYSTEMS Pty Ltd.****Australia**

105 Lewis Road  
Victoria 3152  
+61 3 98011906  
info@seifertsystems.com.au

**SEIFERT SYSTEMS Ltd.****China**

Unit D8 on 14/F Mai Wah  
Industrial Building  
Nos.1/7 Wah Sing Street  
Hongkong  
+852 91629566  
info@seifertsystems.cn

