

Filter Fan



Description


Order Number:	4023A3000
Brand Name:	SOLIFLEX
Color:	RAL 7035
Housing Material:	ABS Plastic
Ingress protection:	IP 54, Type 12, 3R
Optional:	# 4023A3003 black
Approvals:	CE, cURus, cULus, CSA

Technical data


Operating temperature range:	14°F - +131°F
Air volume flow unimpeded:	15 cfm
Static pressure:	0.16 inH2O @ 50 Hz 0.23 inH2O @ 60 Hz
Dimension H x W x D:	4.2 x 4.2 x 3.1 inch
Weight:	0.54 kg
Cut out dimensions:	3.6 x 3.6 (+0.06) inch
Voltage / Frequency:	120 V ~ 60 Hz
Rated current:	0.13 A
Power consumption:	10 W
Degree of separation:	85% - DIN 24185
Wall thickness:	0.04 - 0.08 in.
Filter class:	G3 according to EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	42 dB(A)

Air flow:

Q = Air flow [m³/h]
P = Static pressure [Pa]



Cut out dimensions:



Order Information

In RAL 9005	4023A3003
With NEMA 3R protection part no.	4023A3030
Taric code	84145915
GTIN (EAN)	5350604100190