

## Filterless enclosure air conditioner




### Description

<b>Order Number:</b>	4269002
<b>Brand Name:</b>	SLIMLINE
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection:</b>	TYPE 12
<b>Approvals:</b>	CE / cURus


## Technical data

<b>Cooling capacity 95F/95F:</b>	1770 BTU
<b>Cooling capacity 95F/122F:</b>	610 BTU
<b>Compressor type:</b>	Rotary piston compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	142 g / 5 oz
<b>High / low pressure:</b>	35 / 30 bar 290 / 188 psig
<b>Operating temperature range:</b>	50°F - 122°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 147 / 383 cfm Cabinet air circuit: 74 / 147 cfm
<b>Mounting:</b>	Wall mounted / Recessed
<b>Dimension H x W x D:</b>	23.6 x 12.6 x 4.3 inch
<b>Weight:</b>	35 lbs.
<b>Cut out dimensions:</b>	22.9 x 11.85 inch
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	2.4 A @ 50 Hz 2.6 A @ 60 Hz
<b>Starting current:</b>	5.8 A
<b>Max. current:</b>	2.8 A
<b>Nominal power 95F95F:</b>	480 W @ 50 Hz 490 W @ 60 Hz
<b>Max. power:</b>	560 W
<b>Fuse:</b>	6 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	5.2 A
<b>Full load current fans:</b>	2.8 A
<b>Connection:</b>	Connection terminal block


**Performance graph:**



**Air flow:**



**Cut out dimensions:**



## Order Information

<b>Verpackungsmaße</b>	680 x 400 x 155 mm
<b>Bruttogewicht</b>	19 kg
<b>Zolltarifnummer</b>	84158200
<b>EAN Nummer</b>	5350604370418