

Thermoelectric cooler




Description

Order Number:	6105313
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data

Cooling capacity 95F/95F:	340 BTU
Air volume flow (system / unimpeded):	Ambient air circuit: 75 / 125 cfm Cabinet air circuit: 27 / 53 cfm
Operating temperature range:	-4°F - 149°F
UL temperature range:	-20°C - 65°C
Mounting:	Recessed
Dimension H x W x D:	11 x 13.9 x 6.9 (4.2 + 2.7) inch
Weight:	21 lbs.
Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	1.0 A
Starting current:	1.6 A
Max. current:	1.2 A
Nominal power 95F95F:	125 W
Max. power:	139 W
Fuse:	2 A (T)
Connection:	4 pole power connector 5 pole connector for signals

Performance graph:



Cut out dimensions:



Order Information

Stainless steel AISI 316 (V4A) housing with chromed heat sinks part no.	61053134
Verpackungsmaße	314 x 436 x 183.5 mm
Bruttogewicht	11.5 kg
Taric code	84158300