

Thermoelectric cooler




Description

Order Number:	6405313
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection to EN 60 529:	IP 66 / UL Type 12, 4, 4X
Approvals:	CE, cURus


Technical data

Cooling capacity 95F/95F:	1370 BTU
Air volume flow (system / unimpeded):	Ambient air circuit: 141 / 191 cfm Cabinet air circuit: 141 / 191 cfm
Operating temperature range:	-4°F - 149°F
UL temperature range:	-20°C - 65°C
Mounting:	Halbeinbau
Dimension H x W x D:	23.6 x 17 x 7.8 (5.2 + 2.6) inch
Weight:	34 kg
Cut out dimensions:	15 x 21.6 inch
Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	4.1 A
Starting current:	6.5 A
Max. current:	4.5 A
Nominal power 95F95F:	490 W
Max. power:	537 W
Fuse:	7 A (T)
Connection:	4 pole power connector 5 pole connector for signals

Performance graph:



Cut out dimensions:



Order Information

Mit Edelstahlgehäuse AISI 316 (V4A) Bestell Nr.	64053134
Verpackungsmaße	686.6 x 454 x 232 mm
Bruttogewicht	38 kg
Zolltarifnummer	84158300