

Thermoelectric cooler




Description

Order Number:	6405315
Brand Name:	SOLITHERM PELTIER
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection:	IP 66 / UL Type 12, 4, 4X
Included:	Kondensatablaufstutzen
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data

Cooling capacity 95F/95F:	1370 BTU
Operating temperature range:	-4°F - 149°F
UL temperature range:	-20°C - 65°C
Air volume flow (system / unimpeded):	Ambient air circuit: 141 / 191 cfm Cabinet air circuit: 141 / 191 cfm
Mounting:	External (with frame)
Dimension H x W x D:	23.6 x 17 x 8 inch
Weight:	82 lbs.
Cut out dimensions:	7.9 x 21.6 inch
Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	4.1 A
Starting current:	6.5 A
Max. current:	4.5 A
Nominal power 95F95F:	490 W
Max. power:	537 W
Fuse:	7 A (T)
Connection:	4 pole power connector 5 pole connector for signals

Performance graph:



Cut out dimensions:



Order Information

Stainless steel AISI 316 (V4A) housing part no.	64053154
Verpackungsmaße	686.6 x 454 x 232 mm
Bruttogewicht	41 kg
Taric code	84158300