

## Outdoor air conditioner




## Description

<b>Order Number:</b>	572001201
<b>Brand Name:</b>	Compact Outdoor
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection:</b>	IP 56 / Type 12, 3, 3R, 4
<b>Included:</b>	Mit Schaltschrankheizung und Aluminium Filter
<b>Approvals:</b>	CE, cURus, cULus
<b>UL File Number:</b>	cURus (SA32278), cULus (E498756)


## Technical data

<b>Cooling capacity 95F/95F:</b>	6825 BTU
<b>Cooling capacity 95F/122F:</b>	5460 BTU @ 50 Hz 5460 BTU @ 60 Hz
<b>Enclosure heater:</b>	1000 W
<b>Compressor type:</b>	Rotary piston compressor
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	460 g / 16.2 oz
<b>High / low pressure:</b>	29.3 / 6.1 bar 425 / 88 psig
<b>Operating temperature range:</b>	-40°F - 131°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 385 / 706 cfm Cabinet air circuit: 235 / 500 cfm
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	45.2 x 15.5 x 10.6 inch
<b>Weight:</b>	106 lbs.
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	5.5 A @ 50 Hz 6.5 A @ 60 Hz
<b>Starting current:</b>	16 A
<b>Max. current:</b>	7.9 A
<b>Nominal power 95F95F:</b>	1,17 kW @ 50 Hz 1,41 kW @ 60 Hz
<b>Max. power:</b>	1,65 kW @ 50 Hz 2,10 kW @ 60 Hz
<b>Fuse:</b>	13 A (T)
<b>Short-circuit current rating:</b>	5 kA
<b>Connection:</b>	Connection terminal block

**Performance graph:**



**Cut out dimensions:**



## Order Information

<b>Box dimensions</b>	1,190 x 443 x 310 mm
<b>Gross weight</b>	52 kg
<b>Taric code</b>	84158200