

## Enclosure air conditioner




## Description

<b>Order Number:</b>	850510S62
<b>Brand Name:</b>	SLIMLINE PRO
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection:</b>	IP 56 / Type 12, 3, 3R, 4, 4X
<b>Approvals:</b>	CE, cURus, cULus


## Technical data

<b>Cooling capacity 95F/95F:</b>	2215 BTU
<b>Cooling capacity 95F/122F:</b>	1350 BTU
<b>EER 95F95F:</b>	1.41
<b>Compressor type:</b>	Rotary piston
<b>Refrigerant / GWP:</b>	R134a / 1430
<b>Refrigerant charge:</b>	103 g / 3.63 oz
<b>High / low pressure:</b>	25 / 6 bar 363 / 87 psi
<b>Operating temperature range:</b>	50°F - 140°F
<b>UL temperature range:</b>	50°F - 131°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 117 / 240 cfm Enclosure circuit: 72 / 106 cfm
<b>Mounting:</b>	Wall mounted / recessed
<b>Dimension H x W x D:</b>	14.6 x 20.5 x 6.2 inch
<b>Weight:</b>	35 lbs
<b>Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>UL Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Current 95F95F:</b>	4.1 A
<b>Starting current:</b>	13 A
<b>Max. current:</b>	5.3 A
<b>Nominal power 95F95F:</b>	460 W
<b>Max. power:</b>	610 W
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	3.7 A
<b>Full load current fans:</b>	0.4 A
<b>Connection:</b>	4 pole terminal block for electrical connection 5 pole terminal block for signals 3 pole terminal block for RS 485

**Performance graph:**



**Cut out dimensions:**



## Order Information

**Box dimensions** 460 x 620 x 181.75 mm

**Gross weight** 20 Kg

**Taric code** 84158200