

Enclosure air conditioner




Description

Order Number:	43250081
Brand Name:	COMPACT INDOOR
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	TYPE 12
Approvals:	CE, cURus, cULus


Technical data

Cooling capacity 95F/95F:	8560 BTU
Cooling capacity 95F/122F:	7160 BTU
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	850 g / 30 oz
High / low pressure:	29.5 / 6 bar 425 / 88 psig
Operating temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 441 / 706 cfm Cabinet air circuit: 323 / 706 cfm
Mounting:	Recessed
Dimension H x W x D:	51 x 21.9 x 13.4 inch
Weight:	143 lbs.
Cut out dimensions:	19.4 x 48.6 inch
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	3.9 A @ 50 Hz 5.3 A @ 60 Hz
Starting current:	23 A
Max. current:	6.6 A
Nominal power 95F95F:	910 W @ 50 Hz 1.16 kW @ 60 Hz
Max. power:	1.19 kW @ 50 Hz 1.48 kW @ 60 Hz
Fuse:	10 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block


Performance graph:



Air flow:



Cut out dimensions:



Order Information

Stainless steel housing part no.	43250026
Taric code	84158200